


405 SERIES, FLEXIBLE CABLE,  
2.4MM(MALE)- G3PO(SMPS)(FEMALE)

**GAH71-24MG3PF-XXX**



\* Label and Shrinking tube design depend on customer's request.

## Configuration

Connector 1 Type	2.4mm Male
Connector 1 Body Style	Straight
Body Material and Plating	Passivated Staindless Steel
Connector 1 Mount Method	None
Connector 2 Type	G3PO(SMPS) Female
Connector 2 Body Style	Straight
Body Material and Plating	CuBe Gold Plated
Connector 2 Mount Method	None
Cable Type	405 Series

## Electrical Specifications

Impedance	50 $\Omega$
Frequency	DC to 50 GHz
Return Loss/VSWR	12 dB to 50 GHz
Phase Stability vs. Flexure	N/A
Amplitude Stability	N/A
Shielding Effectiveness	<-100dB @ 1GHz
Phase Matching	On request
Signal Delay	On request
Power Handling	110watt @ 2GHz at sea level,VSWR1.0

## Environmental Data

Temperature Range	-40°C to +165°C
2002/95/EC(RoHS)	Compliant

**Cable Specifications**

Center Conductor	Silver plated copper
Dielectric	Solid PTFE
Jacket	FEP
Capacitance(pF/m)	96.1
Velocity of propagation(%)	70
Min. bending radius(mm)	6.35
Jacket Diameter(mm)	2.64±0.13

**Part Number List**

Part Number	Length [mm]	Insertion Loss ≤(dB)			
		5GHz	10GHz	20GHz	40GHz
GAH71-24MG3PF-1000	1000±10	1.7	2.5	3.8	6.9
GAH71-24MG3PF-800	800±8	1.4	2.06	3.14	5.66
GAH71-24MG3PF-600	600±6	1.09	1.64	2.48	4.32
GAH71-24MG3PF-500	500±5	0.95	1.42	2.15	3.82
GAH71-24MG3PF-300	300±5	0.65	0.96	1.49	2.56
GAH71-24MG3PF-260	260±5	0.59	0.87	1.35	2.31
GAH71-24MG3PF-200	200±5	0.51	0.74	1.16	1.94
GAH71-24MG3PF-100	100±5	0.35	0.52	0.83	1.32

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty or our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.