



* Label and Shrinking tube design depend on customer's request.

Configuration

Connector 1 Type	TRB Male
Connector 1 Body Style	Straight
Body Material and Plating	Brass Trimetal Plated
Connector 1 Mount Method	4 Hole Flange
Connector 2 Type	BNC Male
Connector 2 Body Style	Right Angle
Body Material and Plating	Brass Nickel Plated
Connector 2 Mount Method	None
Cable Type	TRC-50-1 Series

Electrical Specifications

Impedance	50 Ω
Frequency	DC to 3 GHz
Phase Stability vs. Flexure	N/A
Amplitude Stability	N/A
Phase Matching	On request
Signal Delay	On request

Environmental Data

Temperature Range	-40°C to +75°C
2011/65/EU(RoHS)	Compliant

Cable Specifications

Center Conductor	Tinned Copper Wire
Dielectric	Solid Clear Polyethylene
Jacket	Yellow polyvinylchloride
Capacitance(pF/m)	29.5
Velocity of propagation(%)	66
Jacket Diameter(mm)	3.96±0.13

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.